(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 25 August 2005 (25.08.2005)

PCT

(10) International Publication Number WO 2005/077571 A1

(51) International Patent Classification⁷:

B22F 3/26

(21) International Application Number:

PCT/US2005/003767

- (22) International Filing Date: 4 February 2005 (04.02.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:

60/542,271 4 February 2004 (04.02.2004) US

- (71) Applicant (for all designated States except US): GKN SINTER METALS, INC. [US/US]; N112 W18700 Mequon Road, Germantown, WI 53022 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BYRD, Kent, L., Jr. [US/US]; 1718 Klerner Lane, New Albany, IN 47150 (US). TAYLOR, Alan [GB/US]; 3006 Wolf Ridge Drive, New Albany, IN 47150 (US).
- (74) Agent: ROCHE, Richard, T.; Quarles & Brady LLP, 411 E. Wisconsin Avenue, Milwaukee, WI 53202 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SHEET MATERIAL INFILTRATION OF POWDER METAL PARTS

(57) Abstract: A powder metal part infiltration process uses a stamped metallic sheet as a source of metal for infiltration to achieve a high strength powder metal part. A powder metal is compacted, and an infiltrant blank is formed from a wrought metal sheet. The infiltrant blank is placed on top of the compact, and the compact is sintered at a temperature sufficient to form a sintered compact with a matrix having pores and to melt the wrought metal such that the melted wrought metal infiltrates the pores of the matrix. The infiltrant blank may be formed with a locating element for engaging a corresponding locating element on the compact to improve positioning of the blank on the compact. Also, the compact may be separately sintered, and the infiltrant blank may then be placed on the sintered compact. The wrought metal is then melted such that the melted wrought metal infiltrates the pores of the matrix.